



# **Indigo™ Series** 450 Ice Cube Machine

Model: ID-0452A J IY-0454A



## Ice Machine Electric

115/60/1 standard. (208-230/60/1 and 230/50/1 also available)

#### Minimum circuit ampacity:

Air-cooled: 13.2 Water-cooled: Maximum fuse size: 20 amps 1ph

## **Specifications**

## **BTU Per Hour:**

5,400 (average) 6,300 (peak)

#### Refrigerant:

R-404A CFC-free

### **Operating Limits:**

- **Ambient Temperature Range:** 35° to 110°F (1.7° to 43.3°C) Water Temperature Range: 35° to 90°F (1.7° to 32.2°C)
- · Water Pressure Ice Maker Water In: Min. 20 psi (137.9 kPA) Max. 80 psi (551.1 kPA)

Designed for operators who know that ice is critical to their business, the Indigo™ Series ice machine's preventative diagnostics continually monitor itself for reliable ice production. Improvements in cleanability and programmability make your ice machine easy to own and less expensive to operate.

☐ IY-0455W

- Space-Saving Design Up to 450 lbs. (204 kgs.) daily ice production and only 30" (76.20 cm) wide.
- Intelligent Diagnostics provide 24 hour preventative maintenance and diagnostic feedback for trouble free operation.
- Acoustical Ice Sensing Probe for reliable operation in challenging water conditions.
- EasyRead Display communicates operating status, cleaning reminders, and asset information through a blue illuminated display.
- Programmable Ice Production by On/Off Time, Ice Volume or Bin Level (with accessory bin level control) further improves energy efficiency and savings.
- Easy to Clean Foodzone Hinged front door swings out for easy access. Removable water-trough, distribution tube, curtain, and sensing probes for fast and efficient cleaning. Select components made with AlphaSan® antimicrobial.
- **DuraTech™ Exterior** provides superior corrosion resistance. Stainless finish with innovative clear-coat resists fingerprints and dirt.
- Available **LuminIce™ Growth Inhibitor** controls the growth of bacteria and yeast within the foodzone.



## Ice Shape





Dice <sup>7</sup>/8" X (2.22 x 2.22 x 2.22 cm)













: ISO 9001:2008 =

2110 South 26th Street PO Box 1720 Manitowoc, WI 54221-1720 USA Tel: 1.920.682.0161 Fax: 1.920.683.7589 www.manitowocice.com







## i-450 on B-400 24.50" (62.23 cm) Storage Bin Installation Note Minimum installation A Top/sides: 8" (20.32 cm); Back is 5" (12.7 cm) 32.00" (81.30 cm) 6.00" (15.24 cm) 34.00" (86.30 cm) 30.00" (76.20 cm) (A) Electrical Entrance (2) Options 1/2" (1.27 cm) Auxillary Base Drain Socket B 3/8" (0.95 cm) F.P.T. Water Condenser Inlet (E) 3/8" (0.95 cm) F.P.T. Ice Making Water Inlet (water-cooled units) ( 1/2" (1.27 cm) F.P.T. Water Condenser Outlet F 1/2" (1.27 cm) F.P.T. Ice Making Water Drain (G) 3/4" (1.91 cm) Bin Drain

# Space-Saving Designs





	i-450 B-400	<b>i-450</b> <b>B-570</b> 71.50" 181.61 cm	
Height	59.50" 151.13 cm		
Width	30.00" 76.20 cm	30.00" 76.20 cm	
Depth	34.00" 86.30 cm	34.00" 86.30 cm	
Bin Storage	290 lbs. 131.7 kgs.	430 lbs. 195.2 kgs.	

Height includes adjustable bin legs 6.00" to 8.00", (15.24 to 20.32 cm) set at 6.00" (15.24 cm).

# Specifications

		Ice	Ice Production 24 Hours		Power Usage kWh/100 lbs. @90°Air/70°F	Water Usage/ 100 lbs. 45.4 kgs. of Ice	ENERGY
	Model	Shape	70°Air/ 50°F Water	90°Air/ 70°F Water	1 Ph	Potable Water	STAR*
AIR-COOLED	ID-0452A	dice	420 lbs.	320 lbs,	6.24	24.4 Gal.	*
			191 kgs.	145 kgs.		92.4 L	
	IY-0454A half-	half-dice	450 lbs.	335 lbs.	5.97	24.4 Gal.	*
			204 kgs.	152 kgs.		92.4 L	
	ID 045314/	dice	430 lbs.	360 lbs.	4.70	24.4 Gal.	NA
JED			195 kgs.	163 kgs.		92.4 L	
WATER-COOLED	IY-0455W half-dice	450 lbs.	360 lbs.	4.70	24.4 Gal.	NA	
		-	204 kgs.	163 kgs.	4.70	92.4 L	INA
M	* Water-cooled Condenser Water Usage / 100 lbs. /45.4 kgs. Of Ice: 169 gal/640 L.  * Water-cooled models are excluded from ENERGY STAR qualification.						

Order ice storage bin separately.

## Accessories

#### LuminIce™ Growth Inhibitor reduces yeast and bacteria growth for a

cleaner ice machine.



Bin Level Control Allows ice bin level to be automatically set. Built-in LED light illuminates bin.



#### Arctic Pure® Water Filters

Reduces sediment and chlorine odors for better tasting ice.



# AuCS®

schedules and performs routine ice machine cleaning automatically.



2110 South 26th Street
PO Box 1720
Manitowoc, WI 54221-1720 USA

Tel: 1.920.682.0161 Fax: 1.920.683.7589 www.manitowocice.com





4768 (replaces 2987E S-450) © 2011 Manitowoc 1/11 Continuing product improvement may necessitate change of specifications without notice