



98001-1 Pre-rinse unit

- 1) Deck mounted type
- 2) Heavy duty construction
- 3) 20"(510mm)riser brass pipe
- 4) 44"(1118mm)flexible stainless steel hose, SANTOPRENE inner pipe
- 5) Spray valve
- 6) 6"(152)Wall bracket
- 7)The product includes check valve to prevent cross-flow
- 8)The spray valve conforms to ANSI/ASTM F2324-03
- 9)Ideal For food service,commercial kitchens, restaurants and hotel applications

(Hose & Spray valve can interchange with T&S)

沖洗龍頭
單孔臺面花灑龍頭，豎起管高度 20" (510mm)，配 44" (1118mm) 不銹鋼雙扣軟管
內管採用美國 NSF 無毒認證材料，配 6" (152mm) 長度牆支架，(花灑 / 軟管可以和 T & S 互配)



98001-2

Pre-rinse unit

- 1)Deck mounted type
- 2) Heavy duty construction
- 3) 20"(510mm)riser brass pipe
- 4) 44"(1118mm)flexible stainless steel hose, SANTOPRENE inner pipe
- 5) Spray valve
- 6) 6"(152)Wall bracket
- 7)The product includes check valve to prevent cross-flow
- 8)Add-on faucet, Swing nozzle with 6"(152mm)length
- 9)The spray valve conforms to ANSI/ASTM F2324-03
- 10)Ideal For food service,commercial kitchens, restaurants and hotel applications

(Hose & Spray valve can interchange with T&S)

沖洗龍頭
單孔臺面花灑龍頭，豎起管高度 20" (510mm)，配 44" (1118mm) 不銹鋼雙扣軟管
內管採用美國 NSF 無毒認證材料，配 6" (152mm) 長度牆支架，配外加龍頭，直管高度 3" (76mm)，配長度 12" (305mm) 的出水管。(花灑 / 軟管可以和 T & S 互配)



98002-1

Pre-rinse unit

- 1)8"(203mm)Center Wall mounted type
- 2)Heavy duty construction
- 3)20"(510mm)riser brass pipe
- 4)44"(1118mm)flexible stainless steel hose, SANTOPRENE inner pipe
- 5)spray valve
- 6)6"(152mm)Wall bracket
- 7)The product includes check valve to prevent cross-flow
- 8)The spray valve conforms to ANSI/ASTM F2324-03
- 9)Ideal For food service,commercial kitchens, restaurants and hotel applications

(Hose & Spray valve can interchange with T&S)

沖洗龍頭
雙孔8"(203mm)對中裝牆式花灑龍頭，豎起管高度 20" (510mm)，配 44" (1118mm) 不銹鋼雙扣軟管
內管採用美國 NSF 無毒認證材料，配 6" (152mm) 長度牆支架，(花灑 / 軟管可以和 T & S 互配)



98002-2

Pre-rinse unit

- 1)8"(203mm)Center Wall mounted type
- 2)Heavy duty construction
- 3)20"(510mm)riser brass pipe
- 4)44"(1118mm)flexible stainless steel hose, SANTOPRENE inner pipe
- 5)spray valve
- 6)6"(152mm)Wall bracket
- 7)The product includes check valve to prevent cross-flow
- 8)Add-on faucet, Swing nozzle with 6"(152mm)length
- 9)The spray valve conforms to ANSI/ASTM F2324-03
- 10)Ideal For food service,commercial kitchens, restaurants and hotel applications

(Hose & Spray valve can interchange with T&S)

沖洗龍頭
雙孔8"(203mm)對中裝牆式花灑龍頭，豎起管高度 20" (510mm)，配 44" (1118mm) 不銹鋼雙扣軟管
內管採用美國 NSF 無毒認證材料，配 6" (152mm) 長度牆支架，配外加龍頭，直管高度 3" (76mm)，配長度 12" (305mm) 的出水管。(花灑 / 軟管可以和 T & S 互配)